



Gertex Nova Tech Super 10W-40

Premium Gasoline Engine Oil

Gertex Nova Tech Super 10W-40 is a multigrade engine oil formulated with high-quality semi-synthetic base oil and suitable additives; it is designed for use in all seasons and weather conditions in various gasoline-powered vehicles manufactured up to 2004.

Key Information:

QUALITY LEVELS	APPLICATION
• API SL • ACEA A3/B4 • MB 229.3 • Renault RN0700 • INSO 22261	Gertex Nova Tech Super 10W-40 engine oil can be used to lubricate gasoline and four-stroke engines manufactured up to 2004, meeting the API SL quality standard.

Customer Benefits:

- Preventing sludge build-up and controls oxidation
- Advanced viscometrics for maximum power and minimum viscous drag
- Fuel saving
- Excellent protection of engine parts against corrosion and rust

Gertex Nova Tech Super 10W-40



Premium Gasoline Engine Oil

Specifications:

Typical Characteristics	Test Method	Result
SAE Grade	-	10W-40
Kinematic Viscosity, cSt @ 40 °C @ 100 °C	ASTM D445	104.9 15.12
Viscosity Index	ASTM D2270	151
Density @ 15, kg/m ³	ASTM D4052	872
Flash Point COC, °C	ASTM D92	222
Pour Point, °C	ASTM D97	-33
TBN, mg KOH/g	ASTM D2896	7.5
CCS, cP	ASTM D5293	6910@-25 °C
Noack, %	ASTM D5800	8.7

* Minor variations in specification values across different samples are unavoidable.

Health and Safety:

- Avoid skin contact with this product; in case of contact, wash immediately with soap and water.
- Avoid discharging used oil into the environment.

Storage and Handling:

- The storage temperature for this product must not exceed 45°C or fall below 5°C.
- Store in a covered area.

Faraz Aseman Parsian Co

www.gertexoil.com

Tel: +982191305654