



Gertex Nova Tech Supreme 5W-30

Premium Gasoline Engine Oil

Gertex nova Tech Supreme 5W-30 is a multi-grade engine oil formulated with high-quality, fully synthetic base oil and appropriate additives; it is designed for use in all seasons and weather conditions across a wide range of gasoline-powered vehicles manufactured from 2010 onwards.

- The storage temperature for this product must not exceed 45°C or fall below 5°C.
- Store in a covered area.

Key Information:

QUALITY LEVELS	APPLICATION
• API SN • ACEA A3/B4 • MB 229.51 • Renault RN0710 • INSO 22261	Gertex nova Tech Supreme 5W-30 engine oil can be used to lubricate the engines of gasoline-powered, four-stroke vehicles (model year 2010 and newer) that meet API SN+/SN quality standards.

Customer Benefits:

- Preventing sludge build-up and controls oxidation
- Advanced viscometrics for maximum power and minimum viscous drag
- Fuel saving
- Excellent protection of engine parts against corrosion and rust
- Low evaporation loss
- Advanced protection of engines operating on alternative fuels such as Ethanol

Gertex Nova Tech Supreme 5W-30



Premium Gasoline Engine Oil

Specifications:

Typical Characteristics	Test Method	Result
SAE Grade	-	5W-30
Kinematic Viscosity, cSt @ 40 °C @ 100 °C	ASTM D445	72.1 11.95
Viscosity Index	ASTM D2270	163
Density @ 15, kg/m ³	ASTM D4052	854
Flash Point COC, °C	ASTM D92	226
Pour Point, °C	ASTM D97	-42
TBN, mg KOH/g	ASTM D2896	8.05
CCS, cP	ASTM D5293	6050@-35 °C
Noack, %	ASTM D5800	8.8

* Minor variations in specification values across different samples are unavoidable.

Health and Safety:

- Avoid skin contact with this product; in case of contact, wash immediately with soap and water.
- Avoid discharging used oil into the environment.

Storage and Handling:

- The storage temperature for this product must not exceed 45°C or fall below 5°C.
- Store in a covered area.

Faraz Aseman Parsian Co

www.gertexoil.com

Tel: +982191305654